

OPEN TRUCK PULLS

WEDNESDAY , AUGUST 24, 2022

ENTRY FEE - \$25.00 PER TRUCK

GENERAL RULES FOR ALL CLASSES

Open to the first 25 to register.

To register e-mail Scott Bond davesequipmentsales@att.net Include your name, address, truck info (year, make, model, engine type)

NOBODY WILL BE ALLOWED TO REGISTER THE DAY OF THE PULL

Registration and inspection will start at 4:30 and will end at 5:30

BE ON TIME! IF YOU ARE NOT THERE BY 5:30 YOU WILL NOT PULL

All drivers must have a valid drivers license

Only the driver can be in the truck when pulling

Nobody is to ride in the back of the truck at anytime

Helmets and seatbelts must be worn while pulling

Headlights **MUST** be turned off while pulling

Driver side window must be down while hooking and pulling

ABC fire extinguisher must be in the cab within reach of the driver

Hitch must be in place when weighing. **EVERY TRUCK MUST HAVE IT'S OWN HITCH**

No clevis hitches. If we can't get the hook in your hitch you can't pull!

ALL TRUCKS MUST HAVE A DRIVESHAFT LOOP to keep the rear driveshaft from coming out in case of failure.

No drugs or alcohol are permitted on the premises

Coolers will be searched by Hunterdon County Park rangers and or the local police patrolling the pit area.

Anyone found with drugs or alcohol will be removed from the fairgrounds

Work Stock Diesel and Gas Truck Rules

8,500 Lb. Max Weight

Must be street legal and registered

D.O.T stamped approved street tires only

No dual wheels. Dually trucks may remove 1 set of rear tires

OEM factory steel body only

All trucks must have a bed that covers the wheels and no longer than 8' in length

Factory frame, no tube chassis front or rear

Must have stock suspension, traction bars are permitted

No air bag suspension. If equipped must be disconnected

1 in. of suspension travel minimum.

OEM Factory transmission and transfer case for make and model truck

Gas or Diesel only no Nitrous Oxide or other fuels or gases injected

Must have factory fuel tank

Exhaust must exit behind the cab, If stock exhaust and Cat have been removed two 3/8 bolts must be put through the exhaust in a cross pattern for diesel trucks

Hitch height 26" max

Hitch must be receiver-style; reinforcements are allowed

Hitch hook point must be the rear most point of the truck and must be rearward of the stock location of the tailgate

Hitch must be stationary in all directions

Weights are permitted. **NO Front hanging weights!**

Weights are permitted in the bed but must be secured

No weights in the cab, No aftermarket weighted bumpers

Open Diesel Trucks

8,000lb Max Weight

Hanging front weight permitted but can not exceed 60" to the furthest most point of the weight to the center line of the front axle

Weight can be added in the bed as long as it is securely fastened

Must be OEM steel truck body

OEM chassis with engine in factory position

OEM transmission and transfer case

Duals are permitted

Exhaust must exit upwards

If stock exhaust has been removed two 3/8 inch bolts minimum grade 5, must be installed in a cross pattern within one inch of each other as close to the turbo as possible.

Hitch height 26

Front suspension must remain stock

Rear suspension may be blocked

Diesel only Nitrous Oxide and propane are prohibited

OEM fuel tank

Hitch height 20in max

All rules are subject to change the day of the pull